

MAGICGRIP® – Basecoat

MAGICGRIP®–Base Coat is single component product for protection of water proof coating on bathroom area, swimming pool area and any wet area application. This product is modified with high polymers giving it a self curing & excellent bonding properties on dense and smooth concrete surface.

PROPERTIES

Magicgrip®–Basecoat has excellent bonding towards the waterproof coating, giving long term adhesion and stability to the waterproof coat. It is a self-curing coating. A thin coat is sufficient to get excellent bonding. It is easy to mix hence doesn't require a skilled labor for mixing or application purpose. You need to follow the below steps and apply with trowel. It gives you a shrink free and crack free smooth coated floor. It's a one component system having good pot life of ~1hour after mixing with water.

This product contains organic and inorganic binders. It has Low-VOC content.

APPLICATIONS

One can apply Magicgrip®–Basecoat on any waterproof coated area like bathroom, terrace, roof slab etc...

1. Take MAGICGRIP®–Basecoat 1kg, add 350 to 400 grams water & mix properly to prepare thick slurry
2. Wait for 5 minutes
3. After 5 minutes remix the material and spread the material on water proof coating surface as protection layer and allow it to dry for 12 hours.

Once this coating is dried completely, you can go ahead with lying tile or brick coba as per your need

1 kg of MAGICGRIP®–Basecoat will cover 3.5 to 4 sq.fts area with 2mm thickness

Additional information

We provide the necessary Testing certificates, if required. The testing is been done through a third party for unbiased results.

PACKING & STORAGE

Packing:
25kg bag

Storage:

As it's a free flowing powder, it is necessary to store it dry place in proper condition. When stored in proper storage condition the shelf life of the product is 6months from the packaging date. Once opened, it should be ensured that the packet is used completely, or ensure it is secured air tight. Do not use open packets which is left open for long time. Also, a proper mixing of bag with hand is recommended before use. In case the packet gets damaged during transportation or due to any other reasons, kindly inform the manufacturer for help. Use the product only if it's free flowing; else report the issue to manufacturer.

SAFETY PRECAUTION

The above mentioned product is non-toxic. However a care should be taken to avoid eye-contact or inhalation. If any irritation occurs kindly consult a physician

Registered Address

A-1, Flat no:601, Yogi Palace,
Yogi nagar, Borivli(west)
Mumbai – 400091
Ph: 9820892938
E-Mail:-becscoating@yahoo.com

Correspondence Address

BECS COATING
Room no 15, Shanti Bhavan Building,
Soni wadi, Near Shimpoli signal
.Borivali (west) Mumbai - 400092
Ph : 9820892938
Email :becscoating@yahoo.com