

MAGICGRIP® FLEX

Magicgrip® Flex is a high polymer modified tile adhesive. It is cementitious, single component dry powder recommended for fixing vitrified tiles, marble, granite etc on walls including dense and smooth concrete walls, swimming pools area and floor area.

PROPERTIES

Magicgrip® Flex has very high tensile adhesion strength, excellent pot life and excellent open time. It has the property of expansion & contraction due to its thixotropic nature; hence delamination of the tile doesn't take place.

One can use less amount of material for fixing tile hence giving low structural load and less material consumption. This gives high productivity. As it's a single component system, you don't require skilled labor for mixing.

It gives you a shrink free and crack free smooth surface for tile application. It's a one component system having good pot life of ~1hour after mixing with water.

This product contains organic and inorganic binders. It has Low-VOC content.

APPLICATIONS

Magicgrip® Flex can be applied for fixing wall and floor tiles on all smooth and dense concrete surfaces, swimming pool area, Tile on Tile application.etc.

1. Mix Magicgrip® Flex 100 parts with clean water 22 to 30 parts to prepare a thick paste.
2. Keep for 5 min.

3. Remix & use immediately within 1 hour time.

1 kg of Magicgrip® Flex covers 3sq.fts (thickness of 3mm)

Additional information

We provide the necessary Testing certificates, if required. The testing is been done through a third party for unbiased results.

PACKING & STORAGE

Packing:

20kg bag, product available in grey & white color.

Storage:

As it's a free flowing powder, it is necessary to store it in a cool dry place in proper condition. When stored in proper storage condition the shelf life of the product is 6months from the packaging date. Once opened, it should be ensured that the bag is used completely, or ensure it is secured air tight. Do not use open bags which is left open for long time. Also, a proper mixing of bag with hand is recommended before use. In case the bag gets damaged during transportation or due to any other reasons, kindly inform the manufacturer for help. Use the product only if it's free flowing; else report the issue to manufacturer.

SAFETY PRECAUTION

The above mentioned product is non-toxic. However a care should be taken to avoid eye-contact or inhalation. If any irritation occurs kindly consult a physician

Registered Address

A-1, Flat no:601, Yogi Palace,
Yogi nagar, Borivli(west)
Mumbai – 400091
Ph: 9820892938
E-Mail:-becscoating@yahoo.com

Correspondence Address

BECS COATING
Room no 15, Shanti Bhavan Building,
Soni wadi, Near Shimpoli signal
.Borivali (west) Mumbai - 400092
Ph : 9820892938
Email :becscoating@yahoo.com