

MAGICGRIP® P

MAGICGRIP®-P is white cement based polymer modified wall putty which gives excellent bonding to the plaster/concrete and a smooth finish to the wall, ready for painting work.

PROPERTIES

Magicgrip®-P gives you below properties.

White smooth glossy finish
Strong adhesion to the plaster/concrete
Increases paint coverage
Ease of application
Durable & water resistance
Anti fungal
Less curing time

This product contains organic and inorganic binders. It has Low-VOC content.

Working Properties at 21° C

PROPERTY	TYPICAL VALUES
Dry Mortar Density	950 – 1050 kg/m ³
Wet Mortar Density	1650 – 1750 kg/m ³
Water : Powder Ratio	40 : 100
Pot Life	3-4 Hrs
Thickness Per coat	0.5-1 mm
Max Thickness of application	1.5 mm (Two Coats)

APPLICATIONS

One can apply Magicgrip®-P on various masonry surfaces like cement plaster, concrete, Gypsum boards, or any other type of boards available in the market.

Ensure that the surface is prepared. The surface should be free from dust, grease, oil or any other loose particles. Brush the surface with a dry paint

Registered Address

A-1, Flat no:601, Yogi Palace,
Yogi nagar, Borivli(west)
Mumbai – 400091
Ph: 9820892938
E-Mail:-becscoating@yahoo.com

brush to remove any particles. Dry and absorbent surfaces should be pre-wetted with clean water.

Take water in a bucket and add the putty in it, mix it with hand to make it lump free paste. Keep adding water & putty slowly and steadily. Approximately you require 9-10L of water for 25kg bag. Mix it thoroughly to make a thick smooth paste. Allow the paste to rest for 5-10 min and then remix before application.

The putty is applied using putty blades.

Apply two coats with maximum thickness of 1.5mm with putty blades. Ensure that the second coat application should be done after 3hrs or first coat is dried completely. Always prepare a required quantity of putty paste and use it within 2-3 hrs. To remove evenness/application mark and to make glossy surfaces before applying paint use water proof emery paper more than 500 number.

MAGICGRIP®-P gives coverage of approx 16 to 20 sft per kg for 2 coats with maximum thickness of 1.5 mm

Coverage will vary depending on absorption, flatness and evenness of substrate.

PACKING & STORAGE

Packing:

20kg bag

Storage:

As it's a free flowing powder, it is necessary to store it dry place in proper condition. When stored in proper storage condition the shelf life of the product is 12 months from the packaging date. Once opened, it should be ensured that the packet is used completely, or ensure it is secured air tight. Do not

Correspondence Address

BECS COATING
Room no 15, Shanti Bhavan Building,
Soni wadi, Near Shimpoli signal
.Borivali (west) Mumbai - 400092
Ph : 9820892938
Email :becscoating@yahoo.com

use open packets which is left open for long time. Also, a proper mixing of bag with hand is recommended before use. In case the packet gets damaged during transportation or due to any other reasons, kindly inform the manufacturer for help. Use the product only if it's free flowing; else report the issue to manufacturer.

SAFETY PRECAUTION

The above mentioned product is non-toxic. However a care should be taken to avoid eye-contact or inhalation. If any irritation occurs kindly consult a physician

Registered Address

A-1, Flat no: 601, Yogi Palace,
Yogi nagar, Borivli (west)
Mumbai - 400091
Ph: 9820892938
E-Mail: becscoating@yahoo.com

Correspondence Address

BECS COATING
Room no 15, Shanti Bhavan Building,
Soni wadi, Near Shimpoli signal
.Borivali (west) Mumbai - 400092
Ph : 9820892938
Email : becscoating@yahoo.com