

MAGICGRIP® – PL

MAGICGRIP®-PL is high polymer modified self curing smooth plaster. It is cementitious, single component dry powder, having properties of excellent bonding on dense and smooth concrete surface.

PROPERTIES

MAGICGRIP®-PL has excellent bonding towards dense and smooth concrete surfaces and ALC blocks, giving long term adhesion and stability to the surface. It is a self-curing smooth plaster. It is suggested for internal plastering only, where there is no chance of water curing. A thin coat is sufficient to get excellent bonding. No hacking is required on the concrete wall and ceiling before application of MAGICGRIP®-PL. This type of plaster can be done on ceiling as well. (~2-3mm)

It gives you a shrink free and crack free smooth plaster. It's a one component system having good pot life of ~1hour after mixing with water.

This product contains organic and inorganic binders. It has Low-VOC content.

APPLICATIONS

MAGICGRIP®-PL can be applied on all smooth and dense concrete surface walls, ceiling area and ALC block surface.

1. Mix 450 grams of water in 1 kg of MAGICGRIP®-PL under stirring, slowly and steadily

2. Keep the mixture for 5-10 minutes after mixing with water
3. Pre wet the surface before application.
4. Apply with trowel

Additional information

We provide the necessary Testing certificates, if required. The testing is been done through a third party for unbiased results.

PACKING & STORAGE

Packing:

25kg bag

Storage:

As it's a free flowing powder, it is necessary to store it in a cool dry place in proper condition. When stored in proper storage condition the shelf life of the product is 6months from the packaging date. Once opened, it should be ensured that the bag is used completely, or ensure it is secured air tight. Do not use open bags which is left open for long time. Also, a proper mixing of bag with hand is recommended before use. In case the bag gets damaged during transportation or due to any other reasons, kindly inform the manufacturer for help. Use the product only if it's free flowing; else report the issue to manufacturer.

SAFETY PRECAUTION

The above mentioned product is non-toxic. However a care should be taken to avoid eye-contact or inhalation. If any irritation occurs kindly consult a physician

Registered Address

A-1, Flat no:601, Yogi Palace,
Yogi nagar, Borivli(west)
Mumbai – 400091
Ph: 9820892938
E-Mail:-becscoating@yahoo.com

Correspondence Address

BECS COATING
Room no 15, Shanti Bhavan Building,
Soni wadi, Near Shimpoli signal
.Borivali (west) Mumbai - 400092
Ph : 9820892938
Email :becscoating@yahoo.com