

MAGICGRIP® – PM

MAGICGRIP®–PM is a ready to use repair mortar which is durable and gives strong bond. Its single component repair mortar which helps in saving time.

PROPERTIES

Magicgrip®–PM is formulated with high class polymer and reinforced fibers, which gives it uniqueness. It gives high thixotropic strength. The volume of the applied mortar is stable in wet and hardened state thus reducing the tendency of cracking. You need to just add water and mix thoroughly before application, which means it gives uniformity to the working site. It's made up with reinforced fibers which help to give a long life to the repair work. This product is formulated with a polymer hence the rebound is minimum.

As its factory made, the labor doesn't need to do any physical mixing of the polymer. They need to just add water and apply. Thus helping to save time and get the work done quickly with uniformity.

APPLICATIONS

Magicgrip®– PM is ideal for horizontal and vertical structural repairs where the thickness is more than 10-12mm. Like repairs on columns and beams or any other structural members.

Before the application of Magicgrip®–PM ensure that the surface is prepared properly. For surface preparation, cut the edges of the repair vertically to a minimum depth of 5mm. Clean the area to remove any loose materials of mortar, dust or grease.

One bag of 25kg is mixed with water (~3.5-4.2liters) and mixed thoroughly to get a lump free, smooth flowing mortar. Keep the mortar to rest for 2-3mintues and then remix before applying. Ensure to surface is damp but without standing water.

To obtain extra strong bonding, the damp surface is primed with MAGICGRIP®–PM (2:1, powder: water) using a brush. And then mortar is applied immediately.

PACKING & STORAGE

Packing:
25kg bag

Storage:
As it's a free flowing powder, it is necessary to store it dry place in proper condition. When stored in proper storage condition the shelf life of the product is 12months from the packaging date. Once opened, it should be ensured that the packet is used completely, or ensure it is secured air tight. Do not use open packets which is left open for long time. Also, a proper mixing of bag with hand is recommended before use. In case the packet gets damaged during transportation or due to any other reasons, kindly inform the manufacturer for help. Use the product only if it's free flowing; else report the issue to manufacturer.

SAFETY PRECAUTION

The above mentioned product is non-toxic. However a care should be taken to avoid eye-contact or inhalation. If any irritation occurs kindly consult a physician

Registered Address

A-1,Flat no:601, Yogi Palace,
Yogi nagar, Borivli(west)
Mumbai – 400091
Ph: 9820892938
E-Mail:-becscoating@yahoo.com

Correspondence Address

BECS COATING
Room no 15, Shanti Bhavan Building,
Soni wadi, Near Shimpoli signal
.Borivali (west) Mumbai - 400092
Ph : 9820892938
Email :becscoating@yahoo.com