

MAGICGRIP® – Topcoat

MAGICGRIP®–Topcoat is a non-cementitious waterproofing coating for terraces and walls. It's formulated with elastomeric acrylic polymers along with synthetic reinforcing fibers. Thus providing a thick, durable membrane for long last waterproofing.

PROPERTIES

Magicgrip®–Topcoat has excellent cracking bridging properties due to elastomeric acrylic polymers. It provides excellent waterproofing upto 7 bars of positive hydrostatic pressure. The reinforced fibers gives it the abrasion resistance required. The polymers helps in giving a strong adhesion to any masonry surfaces.

It's easy to use, single component system. No dilution at all. 3coats of the product gives long term waterproofing. The drying time between each layer is ~4-6hours.

APPLICATIONS

Magicgrip®– Topcoat is ideal for leaking terraces, roofs, parapet, sunshades and exterior walls or any other masonry surface where water can seep through, and you want to protect the surface by waterproofing.

However it is important to note that the surface is prepared properly before applying. In case, it's a new plastered surface ensure proper curing is been done for 28days and the area will not have any water logging. The slopes are given properly for the water drainage.

The area should be free of any loose mortar, paint, dust or grease. Proper water jet or vacuum cleaner should be used so that the coating should not peel off later.

Need to check for any cracks. If there are cracks which are less than 3mm then fill them up with crack sealer or if the cracks are bigger and deeper then damaged portions should be removed and plastered with PMC (Magicgrip® PM).

For better results, we suggest the use of fiber mesh between the coats. This helps in forming a membrane like structure giving more durability.

PACKING & STORAGE

Packing:

20kg/5kg

Storage:

As it's a liquid polymer, it is necessary to store it in a cool & dry place in proper condition. When stored in proper storage condition the shelf life of the product is 6months from the packaging date. Once opened, it should be ensured that the bucket is used completely, or ensure it is secured air tight. Do not use open buckets which is left open for long time. Film formation may occur causing change in the stability of the product. Also, a proper mixing of the bucket is recommended before use, from top to bottom. In case the bucket gets damaged during transportation or due to any other reasons, kindly inform the manufacturer for help. Use the product only if its sealed packed and there is no film formation; else report the issue to manufacturer.

SAFETY PRECAUTION

The above mentioned product is non-toxic. However a care should be taken to avoid eye-contact or inhalation. If any irritation occurs kindly consult a physician

Registered Address

A-1,Flat no:601, Yogi Palace,
Yogi nagar, Borivli(west)
Mumbai – 400091
Ph: 9820892938
E-Mail:-becscoating@yahoo.com

Correspondence Address

BECS COATING
Room no 15, Shanti Bhavan Building,
Soni wadi, Near Shimpoli signal
.Borivali (west) Mumbai - 400092
Ph : 9820892938
Email :becscoating@yahoo.com