

# MAGICGRIP® 76

MAGICGRIP<sup>®</sup> 76 is a ready to use an aqueous dispersion. It is used for coating of the back side of vitrified tiles, marble and granite to increase its bonding and water resistance.

**PROPERTIES** 

Magicgrip<sup>®</sup>76 is used as a primer for vitrified tiles, marble and granite for increased adhesion and water resistance. It is used for back coating of the tiles, which helps to retain the bond with tiles even after long exposure to water. Such type of coating gives long term durability to the customer. In addition, its ease of application by roller helps to get the job done quickly at the site.

## **APPLICATIONS**

Magicgrip<sup>®</sup> 76 is a ready to use product and is used directly one coat on the backside of the tile, marble & granite.

This can be used along with any other tile adhesive to increase its adhesion and water resistance.

Back coating of tile	Tile adhesive	Classification/ Test result
Magicgrip <sup>®</sup> 76	Cement +sand	C1
Magicgrip® 76	Magicgrip <sup>®</sup> (C1)	C2
Magicgrip <sup>®</sup> 76	Magicgrip <sup>®</sup> Flex (C2)	C3

We also suggest, to apply Magicgrip<sup>®</sup>76 on the wall along with the back coating on the tile to get better results.

### Additional information

We provide the necessary Testing certificates, if required. The testing is been done through a third party for unbiased results.

#### **PACKING & STORAGE**

#### **Packing:**

1kg,5kg,20kg

### **Storage:**

As its dispersion, it is necessary to store it in proper condition. When stored in proper storage condition the shelf life of the product is 6months from the packaging date. Once opened it should be ensured that the drum is not left open for a longer period of time. Also, a proper stirring is recommended from top to bottom before use. Iron or galvanized equipment or containers are not recommended. Therefore, we suggest the use of plastic, ceramic, rubberized or enameled materials. As polymer dispersions are prone to skin formation, store it in a dry place away from sunlight.

#### SAFETY PRECAUTION

The above mentioned product is non-toxic. However a care should be taken to avoid eye-contact or inhalation. If any irritation occurs kindly consult a physician

Registered Address A-1,Flat no:601, Yogi Palace, Yogi nagar, Borivli(west) Mumbai – 400091 Ph: 9820892938

E-Mail:-becscoating@yahoo.com

Correspondence Address

BECS COATING Room no 15, Shanti Bhavan Building, Soni wadi, Near Shimpoli signal Borivali (west) Mumbai - 400092 Ph: 9820892938

Email:becscoating@yahoo.com